INDOOR

tgs

Date:	
Project Name:	
Sku #:	

HELIX™ S

Flush Mounted Square Fixture

APPLICATIONS

Residential, Commercial, Multi-Family, Hospitality

FEATURES

Construction

- Die-cast Aluminum Base
- Spun Aluminum Body

Optical

- Beam Angles:
  - 15°
  - 30°
  - 45°

Electrical & Technical

- Input Voltage: 100-277V
- Input Frequency: 50/60Hz
- Projected Life: L70 > 50,000 hrs
- PF: >0.9
- CRI: >90
- THD: <20%
- CCT: 2700K, 3000K, 4000K, 5000K
- Operating Temp.: -40°F~122°F
- Dry Location

Installation/Mounting

- Pendant Mount:
  - Cable Adjustable to 3.3ft
  - 3.3' Stem [Standard] [Custom Length*]
- Surface Mount

Controls

- Triac Dimming [Option]
- 0-10 Dimming [Option]

Warranty

- 5 Year Warranty
  See warranty documentation for more information.

Lumen Output

- 15W: 1,200lm
- 20W: 1,600lm
- 30W: 2,400lm

HOUSING FINISHES

REFLECTOR FINISHES

90+ CRI · Dry Location · Intertek · CALIFORNIA JA8 TITLE 24 COMPLIANT LAMP

ORDERING INFORMATION

EXAMPLE: HXS-0305-15-30-15-D-BK-WH-CM

HXS

Series	Size	Wattage	CCT	Beam Angle	Dimming	Finish	Reflector	Mounting Option
HXS	0305 - L: 3" x W: 3" x H: 5" 0306 - L: 3" x W: 3" x H: 6" 0406 - L: 4" x W: 4" x H: 6"	15 - 15W 20 - 20W 30 - 30W	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K	15 - 15° 30 - 30° 45 - 45°	D - Triac Dimming D1 - 0-10V Dimming	BK - Black WH - White	BK - Black WH - White SV - Mirror MBK - Matte Black MWH - Matte White MSV - Matte Silver MBZ - Matte Bronze CP - Champagne RG - Rose Gold GD - Gold	CM - Cable Mount [3.3'] ST - Stem Mount [3.3'] SM - Surface Mount

HELIX™ S

Flush Mounted Square Fixture

DIMENSIONS

Pendant Mount







Surface Mount





LUMEN OUTPUT

SKU	Size [LxWxH] (in)	Wattage (W)	Delivered Lumens (lm)	Efficacy (lm/W)
HXS-0305-15-30-15-D-BK-WH-XX	3 x 3 x 5.5	15	1200	80
HXS-0306-20-30-15-D-BK-WH-XX	3.75 x 3.75 x 5.8	20	1600	70
HXS-0406-30-30-15-D-BK-WH-XX	4.5 x 4.5 x 6	30	2400	80

9601 Variel Ave, Chatsworth, CA 91311
(818) - 206 - 4404

Specifications & dimensions subject to change without notice.
*MOQ & longer lead times may apply, please contact customer service for more information.