INDOOR

tgs

Date:	
Project Name:	
Sku #:	

HELIX™ R

Flush Mounted Round Fixture

APPLICATIONS

Residential, Commercial, Multi-Family, Hospitality

FEATURES

Construction

- Die-cast Aluminum Base
- Spun Aluminum Body

Optical

- Beam Angles:
  - 15°
  - 30°
  - 45°

Electrical & Technical

- Input Voltage: 100-277V
- Input Frequency: 50/60Hz
- Projected Life: L70 > 50,000 hrs
- PF: >0.9
- CRI: >90
- THD: <20%
- CCT: 2700K, 3000K, 3500K, 4000K
- Operating Temp.: -40°F~122°F
- Dry Location

Installation/Mounting

- Pendant Mount:
  - Cable Adjustable to 3.3ft
  - 3.3' Stem [Standard] [Custom Length*]
- Surface Mount

Controls

- Triac Dimming [Option]
- 0-10 Dimming [Option]

Warranty

- 5 Year Warranty
  See warranty documentation for more information.

Lumen Output

- 15W: 1,200lm
- 20W: 1,600lm
- 30W: 2,400lm
- 40W: 3,200lm

HOUSING FINISHES

Black White

REFLECTOR FINISHES

Black White Mirror Matte Black

Matte White Matte Bronze Champagne Rose Gold

Gold

90+ CRI Dry Location Intertek JA8 TITLE 24 COMPLIANT LAMP

ORDERING INFORMATION

EXAMPLE: HXR-0305-15-30-15-D-BK-WH-CM

HXR

Series	Size	Wattage	CCT	Beam Angle	Dimming	Finish	Reflector	Mounting Option
HXR	0305 - D: 3"x H: 5"	15 - 15W	27 - 2700K	15 - 15°	D - Triac Dimming	BK - Black	BK - Black	CM - Cable Mount [3.3']
	0305 - D: 3"x H: 5"	20 - 20W	30 - 3000K	30 - 30°	D1 - 0-10V Dimming	WH - White	WH - White	ST - Stem Mount [3.3']
	0405 - D: 4"x H: 5"	30 - 30W	35 - 3500K	45 - 45°			SV - Mirror	SM - Surface Mount
	0506 - D: 5"x H: 6"	40 - 40W	40 - 4000K				MBK - Matte Black	
							MWH - Matte White	
							MSV - Matte Silver	
							MBZ - Matte Bronze	
							CP - Champagne	
							RG - Rose Gold	
							GD - Gold	

9601 Variel Ave, Chatsworth, CA 91311
(818) - 206 - 4404

Specifications & dimensions subject to change without notice.
*MOQ & longer lead times may apply, please contact customer service for more information.

HELIX™ R

Flush Mounted Round Fixture

DIMENSIONS

Pendant Mount



Surface Mount



LUMEN OUTPUT

SKU	Size [DxH] (in)	Wattage (W)	Delivered Lumens (lm)	Efficacy (lm/W)
HXR-0305-15-30-15-D-BK-WH-XX	ø3 x 6	15	1200	80
HXR-0305-20-30-15-D-BK-WH-XX	ø3.75 x 6	20	1400	70
HXR-0405-30-30-15-D-BK-WH-XX	ø4.5 x 6	30	2400	80
HXR-0506-40-30-15-D-BK-WH-XX	ø5.6 x 6	40	3200	80

9601 Variel Ave, Chatsworth, CA 91311
(818) - 206 - 4404

Specifications & dimensions subject to change without notice.
*MOQ & longer lead times may apply, please contact customer service for more information.