

Date:	
Project Name:	
SKU #:	

Double Ring Round Fixture
Flush Mounted Ceiling Light



APPLICATIONS

Residential, Commercial, Multi-Family Complex

FEATURES

Construction

- Die-formed Cold-Rolled Steel
- Powder Coated Paint

Finish

- Brushed Nickel
- Black*
- White*
- Oil Rubbed Bronze*

Electrical & Technical

- Input Voltage: 120V
- Input Frequency: 60Hz
- Projected Life: L70 > 50,000 hrs
- PF: >0.95
- CRI: >80 or >90 [Option]
- THD: <20%
- CCT Selectable: 3000K/4000K/5000K
- Operating Temp.: -4 °F ~ 104 °F
- Damp Location Rated

Optical

- High Transmission Acrylic Lens

Installation/Mounting

- Flush Mount

Controls

- Triac Dimming

Compliance

- JA8 TITLE 24 Compliant at 90CRI

Dimmer Compatibility List:

Leviton: IPL06-10Z, 6672-1LW, 6674-POW, DLS06-1LZ
Lutron: TGCL-153P, MACL-153M, CTCL-153P, PD-6WCL

Lumen Output

- 12"/15W: 1,400lm
- 14"/25W: 2,300lm
- 16"/25W: 2,300lm
- 18"/30W: 2,700lm

Warranty


- 5 Year Warranty
See warranty documentation for more information.



ORDERING INFORMATION **EXAMPLE: DRRC-1215-CC-SN**


DRRC				
Series	Size/Wattage	CCT	Finish	CRI
DRRC	1215 - 12"/15W 1425 - 14"/25W 1625 - 16"/25W 1830 - 18"/30W	CC - 3000K/4000K/5000K	BN - Brushed Nickel BK - Black* WH - White* OB - Oil Rubbed Bronze*	90CRI [Option]

DIMENSIONS




ø12"

Weight: 2.00 lb.




3.40"




ø14"

Weight: 2.98 lb.




3.90"




ø16"

Weight: 2.98 lb.




4.25"



ø18"

Weight: 23.70 lb.



4.70"

LUMEN OUTPUT

SKU	Size (in)	Wattage (W)	Delivered Lumens (lm)	Efficacy (lm/W)
DRSM-1215-CC-XX	12	15	1400	93
DRSM-1425-CC-XX	14	25	2300	92
DRSM-1625-CC-XX	16	25	2300	92
DRSM-1830-CC-XX	18	30	2700	90