

WARNING

PLEASE READ ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION

- To prevent personal injury or product damage only licensed electricians should install.
- To avoid electric shock or component damage disconnect power before attempting installation or servicing.
- This product must be installed in accordance with the national electric code (NEC) and all applicable federal, state and local electric codes and safety standards.
- Disconnect product and allow cooling prior to servicing.
- Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
- To prevent product malfunction and/or electrical shock this product must be properly grounded.
- Wet Location Rated

Installation

1. Turn off the power at the circuit breaker or fuse box. Before beginning installation.
2. Loosen the screw above and below the base to remove the mounting bracket.
3. Secure the mounting bracket to the j-box .
4. Strip the 1/2 inch insulation from the wire ends. Twist striped ends together with pliers. Brown to Black (Power) and Blue to White (Neutral). Attach Yellow wire to ground wire . If necessary, attach copper ground wire to the outlet box ground.
5. Place the fixture to the mounting bracket and re-install the mount screw to secure the fixture
6. Turn on the power at the circuit breaker or fuse box. Turn the lights switch ON to activate the fixture.

